



Trusted
radiation
protection.

940-9 Portable Continuous Air Monitor

The Code of Federal Regulations requires assurance that radioactive materials within gaseous effluents do not exceed maximum permissible concentrations (MPC) as set forth in the United States Nuclear Regulatory Commission (USNRC) radiation protection standards. This simply means that any effluent that could possibly contain radioactivity must be monitored. Besides the legal implications, sound industrial hygiene practices require that personnel be protected against the possibility of exposure to excessive radioactivity from any source.

Off-line gas monitors are frequently used in conjunction with particulate monitors. This is particularly the case with a stack or duct where effluent is released into the environment. Used in this manner, the particulate monitor serves as a pre-filter for the gaseous monitor and also as a monitor of airborne radioactive particulates. Where an off-line gas monitor is used

independently, without the aid of a particulate monitor, a separate filter assembly is installed to prevent contaminated particulate buildup inside the sensitive volume. The off-line effluent monitor incorporates its own pumping system to insure a positive displacement of the effluents being monitored.

Off-line effluent monitoring is normally utilized where optimum geometry is desired to gain maximum sensitivity. Scintillation crystal detectors are used because of their sensitivity and reliability. Applications The 940-9 provides all of the functions of the 940-1 Off-Line Gaseous Effluent Monitor, in



Key features

- Mounted on heavy-duty casters to enhance mobility
- Self-contained portable air monitor
- Compatible with the 943 Series detectors and the 942A Series or the 960 Series electronics
- Universal Digital Ratemeter with dynamic range up to 10^7 CPM
- Scintillation type detectors
- Rugged construction for ease of maintenance
- Positive displacement type pumping system
- Automatic pressure compensation for gas density monitor
- Automatic purge of sampling system

a portable configuration. The detector output signal is transmitted to the Universal Digital Ratemeter. The particulate rate-meter displays gross particulate counts, iodines are absorbed in an easily removable cartridge, and the gas ratemeter displays gross noble gas counts, compensated for changes in pressure at the volume chamber. These ratemeters also provide output alarm contacts for Alert, High Radiation, Channel Fail, and when required, Rate Of Rise for fixed filter application. A Low Flow alarm is also available for the sample stream. Check source actuation is manual from the ratemeter, with alarms muted when in the check source mode.

Technical specifications

Power requirements

120 V ac, 50/60 Hz, 1 phase

Sample flow rate

1 to 4 SCFM

Sample temperature limit

32 °F to 122 °F (0 to 50 °C)

Sample inlet

0.75 inch OD stainless steel tubing, compression fitting

Sample outlet

0.75 inch OD stainless steel tubing, compression fitting

Maximum internal pressure

10 psig

Dynamic count range

10 to 10⁷ CPM

Skid weight

950 lb

Particulate filter paper

Hollingsworth & Voss
#LB-5211-A-0 with a collection efficiency of 97% for particles 0.3 micron and larger

Iodine filter

TEDA impregnated charcoal cartridge

Note: Optional grab sampling capability available for particulate, iodine, noble gas, and tritium

Ordering information

Model

940-9: Portable Continuous Air Monitor



6045 Cochran Road
Cleveland, OH 44139-3303 U.S.A.

For more information, please contact us at:

Phone: 440-542-3628
Email: Sales@Victoreen.com
Web access: www.victoreen.com

©2015 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A.
5/2015 6003855b_en

Modification of this document is not permitted without written permission from Fluke Corporation.